

Sublimation Ink Data Sheet

Dye Sublimation Ink for Piezo head DX4,5,7 TFP HEAD

For printer	Epson stylus pro series, F7000 series, Mutoh series, Roland FJ, XF series (DX4,5, DX7, TFP head)					
Media	Transfer Sublimation paper					
Application	Printing on polyester, every substrates (wood, ceramics, glass) overprinted with polyester based coatings					
Color specification	Color	Solid cont. (%)	pH	Viscosity (cps)	Surface Tension (dyne/cm)	Particle size (nm)
	Y	2.5	7.5	3.6	26.0 ~ 30.0	120 ~ 160
	M	5.0	7.7	4.2	26.0 ~ 30.0	120 ~ 160
	C	4.8	8.0	4.1	26.0 ~ 30.0	120 ~ 160
	K	5.5	7.8	4.2	26.0 ~ 30.0	120 ~ 160
	* Option color : LC, LM, LK, LLK					
The optimal printing conditions	20~22°C/68~72°F and relative humidity ≥ 60%					
Transfer / Fixation	with hot presses or cylinders : 30~60sec at 190~200°C					
Life Time	1 year					
Caution	Use only for piezo head printer. Don't store inks in high or freezing temperatures. Keep inks out of direct sunshine.					